



Selection Guide

Signal Monitors



Signal Monitor Selection Guide

PRODUCT FAMILY	VECTORSCOPES			WAVEFORM MONITORS				DIGITAL MONITORS			
	1720/ 1721	1725	1720 SCH/ 1721 SCH	1710J/ 1711J	1730/ 1731	1735	1730D	WFM 601A	WFM 601E	WFM 601M	SDA 601
VIDEO STANDARDS											
NTSC; 525/60	X (1720)	X	X (1720 SCH)	X (1710J)	X (1730)	X	X	X	X	X	X
PAL; 625/50	X (1721)	X	X (1721 SCH)	X (1711J)	X (1731)	X		X	X	X	X
Dual Standard 525/625		X				X		X	X	X	X
SIGNAL INPUTS											
Composite Analog	2	2	2	2	2	2	2				
Component Analog (CAV)											
Serial Digital Composite							2				
Serial Digital Component								2	2	2	1
Parallel Digital							X				
High Impedance Probe											
Stereo Audio	X	X	X				X	X			
SIGNAL OUTPUTS											
Analog Picture Monitor				X	X	X	X	X	X	X	X
Digital Picture Monitor								X	X	X	
Line Select Strobe					X	X	X				
Alarm								X	X	X	X
SIGNAL DISPLAYS											
Waveform				X	X	X	X	X	X	X	
RGB/YRGB Parade					X	X	X*4	X	X	X	
Waveform Difference								X	X	X	
VITS Monitoring/Line Select	X*5	X*5	X*5		X	X	X	X	X	X	
Composite Vector	X	X	X								
Component Parade/Overlay								X	X	X	
Component Vector/Lightning/Bowtie								X	X	X	
Diamond (RGB)								X	X	X	
Arrowhead NTSC/PAL GAMUT								X	X	X	
Picture Monitor								X	X	X	
R-Y Sweep	X*7	X*7	X*7								
Eye Pattern (Serial Digital)							X		X	X	
Signal Level/Digital Jitter Readout										X	
Data Logic Analyzer										X	X
Polar SCH Phase			X								
Audio Phase/Amplitude	X	X	X					X			
Frozen Waveform								X	X	X	
MISCELLANEOUS											
Measurement Cursors								X	X	X	
Bandwidth (MHz)	6	6	6	6	6	6	5.5	X*9	X*9	X*9	
Vertical Magnification (# Times)				5	5	5	5	10	10	10	
Remote PC Display											X
Error Alarm							X	X	X	X	X
12 V DC Power											X
Safety/EMI Certified*11	X	X	X	X	X	X	X	X	X	X	X
CONTROL INTERFACE											
User Presets	X*5	X*5	X*5		X	X	X	X	X	X	X
Functions											X
DC Logic Levels	X*5	X*5	X*5		X	X	X	X	X	X	
RS-232C								X	X	X	
Physical Characteristics	*20	*20	*20	*20	*20	*20	*20	*20	*20	*20	*20

Footnote legend on page 4.

Signal Monitor Selection Guide

PRODUCT FAMILY	HDTV		COMBINATION WAVEFORM MONITOR/VECTORSCOPE						COMPONENT/COMPOSITE		
	WFM 1125	1735HD	WFM 90 WFM 91	1740A 1741A	1745A	1750A 1751A	1755A	WVR 500	1760 1761	1765	WFM 300A
VIDEO STANDARDS											
NTSC; 525/60	X		X (WFM 90)	X (1740A)	X	X (1750A)	X	X	X (1760)	X	X*19
PAL; 625/50	X		X (WFM 91)	X (1741A)	X	X (1751A)	X	X	X (1761)	X	X*19
Dual Standard 525/625	X				X			X		X	X*19
HDTV Rates	X*21	X									
SIGNAL INPUTS											
Composite Analog		6	1	8	8	8	8	2	8	8	1
Component Analog (CAV)		2		2	2	2	2		2	2	1
Serial Digital Component		2*22									
Stereo Audio			X*15	X	X	X	X		X	X	
SIGNAL OUTPUTS											
Analog Picture Monitor	X	X*24	X	X	X	X	X	X	X	X	X
Digital Picture Monitor	X										
Rasterized Display	X		X					X			
Extracted AES/EBU Audio	X										
Line Select Strobe	X										
Alarm	X										
SIGNAL DISPLAYS											
RF Spectrum (L Band/70 MHz)		X									
Waveform	X	X	X	X	X	X	X	X	X	X	X
RGB/YRGB Parade	X	X		X	X	X	X		X	X	
Waveform Difference	X*23	X							X	X	X
VITS Monitoring/Line Select	X	X	X	X	X	X	X		X	X	X
Composite Vector			X	X	X	X	X	X	X	X	
Component Parade/Overlay	X	X		X	X	X	X		X	X	X
Component Vector/Lightning/Bowtie	X								X	X	X
Diamond (RGB)	X							X	X		
Picture Monitor			X*16	X	X	X	X	X*18	X	X	
R-Y Sweep				X	X	X	X		X	X	X
Longitudinal Time Code				X	X	X	X		X	X	
Data Logic Analyzer	X										
Polar SCH Phase						X	X		Opt.	Opt.	
Audio Phase/Amplitude			X*17	X	X	X	X		X	X	
Frozen Waveform	X										
MISCELLANEOUS											
Measurement Cursors	X			X	X	X	X		X	X	
Bandwidth (MHz)	30	30	6	10	10	10	10	6	10	10	6
Vertical Magnification (# Times)	10	5	5	10	10	10	10	5	10	10	5
Error Alarm	X		X					X			X
12 V DC Power			X								
Safety/EMI Certified*11	X	X	X	X	X	X	X	X	X	X	X
CONTROL INTERFACE											
User Presets	X	X		X	X	X	X	X	X	X	X
DC Logic Levels	X	X		X	X	X	X		X	X	X
RS-232C	X			X	X	X	X	X	X	X	
Physical Characteristics	*20	*20	*20	*20	*20	*20	*20	*20	*20	*20	*20

Signal Monitor Selection Guide

PRODUCT FAMILY	MEASUREMENT SETS			RF
	1780R 1781R	VM100 VM101	VM700T	1705A
MODEL NUMBER				
VIDEO STANDARDS				
NTSC; 525/60*1	X (1780R)	X (VM100)	Opt. 01	
PAL; 625/50*1	X (1781R)	X (VM101)	Opt. 11	
Dual Standard 525/625			Opt. 01/11	
SIGNAL INPUTS				
Composite Analog	4	1	3	
Component Analog (CAV)	1		1 Opt. 30	
High Impedance Probe	X		Opt. 1Z	
Stereo Audio	X		Opt. 40/41	
SDI			X	
SIGNAL OUTPUTS				
Analog Picture Monitor	X			
SIGNAL DISPLAYS				
RF Spectrum (L Band/70 MHz)				X
Waveform	X		X	
RGB/YRGB Parade	X		Opt. 30	
Waveform Difference	X		X	
VITS Monitoring/Line Select	X		X	
Composite Vector	X		X	
Component Parade/Overlay	X		Opt. 30	
Component Vector/Lightning/Bowtie	X*6		Opt. 30	
Picture Monitor	X		X	
Polar SCH Phase	X		X	
Audio Phase/Amplitude	X		Opt. 40/41	
Measurement Results List		X	X	
Video Wander			X	
MISCELLANEOUS				
Measurement Cursors	X		X	
Bandwidth (MHz)	20	5	6	950-1800*10
Vertical Magnification (# Times)	5		≈300	
Remote PC Display		LIST	VMREMGR	
Precision Audio Measurements			Opt. 40/41	
Measurement Routines	X	X	X	
Automatic Measurements		X	X	
Error Alarm		X	X	
Safety/EMI Certified*11	X	X	X	X
CONTROL INTERFACE				
User Presets	X		X	
Functions			X	
DC Logic Levels	X			
RS-232C	X	X	X*12	
Physical Characteristics	*20	*20	*20	*20

MODEL NUMBER	DIMENSIONS			NET WEIGHT (lbs./kg)
	Height*13 (in./mm)	Width*14 (in./mm)	Depth (in./mm)	
1705A	3U	Half	18.1/460	8.5/3.8
1720/21/25	3U	Half	18.1/460	8.5/3.8
1720SCH/21SCH	3U	Half	18.1/460	8.5/3.8
1710B/11B	3U	Half	18.1/460	8.0/3.6
1730/31/35	3U	Half	18.1/460	8.5/3.8
1730D	3U	Half	18.1/460	9.0/4.0
1735HD	3U	Half	18.1/460	10.3/4.7
1740A/41A	3U	Half	18.1/460	9.0/4.0
1745A	3U	Half	18.1/460	9.4/4.2
1750A/51A/55A	3U	Half	18.1/460	9.4/4.2
1760/61/65	3U	Half	18.1/460	10.0/4.5
1780R/81R	3U	Full	18.1/460	28/12
SDA601	7.5/191	3.6/91	2.2/56	1.5/0.68
VM100/101	1U	Half	18.4/460	4/1
VM700T	5U	Full	21.9/556	45/20
WFM90/91	9.6/244	5/127	3.2/81	3/1.4
WFM300A	3U	Half	18.1/460	9.0/4.0
WFM601/601i	3U	Half	18.1/460	9.0/4.0
WFM601M	3U	Half	18.1/460	9.0/4.0
WFM1125	3U	Half	18.1/460	9.0/4.0
WVR500	1U	Half	18.1/460	4/1.8

Footnotes


- *1 VM700T must be ordered with one of these options.
- *2 With optional Probe Adapter (Tektronix P/N 067-1429-00).
- *3 Left, right, auxiliary inputs.
- *4 Analog inputs only.
- *5 When connected to appropriate 173X Waveform Monitor.
- *6 Bowtie only.
- *7 Output to waveform monitor.
- *8 LED bar graphs for precise level setups; PPM ballistics.
- *9 Accepts signals conforming to CCIR 601 standard.
- *10 45 MHz to 100 MHz on separate input.
- *11 UL-1244/CSA Listed, FCC 15J (Class A), VDE 0871.5 (Class B), 89/336/ECC.
- *12 GPIB and SLIP available as options.
- *13 3U = 3 rack units (5.25 in./132 mm) 5U = 5 rack units (8.75 in./220 mm).
- *14 Half = Half rack width (8.1 in./206 mm) Full = Full rack width (19.0 in./483 mm).
- *15 Displays one audio channel.
- *16 Color display.
- *17 Amplitude only.
- *18 Displays on color monitor.
- *19 Select graticule option for desired NTSC or PAL format.
- *20 See Physical Characteristics table.
- *21 60 or 59.94 Hz field rates:
Opt. 0A, SMPTE 274M, 1920 x 1080 interlaced.
Opt. 0B, SMPTE 296M, x 720 progressive.
Opt. 0C, Dual standard, 1080i/720p.
- *22 SMPTE 292M, 1.485 Gb/s.
- *23 Waveform Save Mode.
- *24 Outputs selected component channel.

For further information, contact Tektronix:

Worldwide Web: For the most up-to-date product information, visit our web site at www.tektronix.com.

ASEAN Countries (65) 356-3900; Australia & New Zealand 61 (2) 9888-0100; Austria, Central Eastern Europe, Greece, Turkey, Malta, & Cyprus +43 2236 8092 0; Belgium +32 (2) 715 89 70;
Brazil and South America 55 (11) 3741-8360; Canada 1 (800) 661-5625; Denmark +45 (44) 850 700; Finland +358 (9) 4783 400; France & North Africa +33 1 69 86 81 81; Germany +49 (221) 94 77 400;
Hong Kong (852) 2585-6688; India (91) 80-2275577; Italy +39 (2) 25086 501; Japan (Sony/Tektronix Corporation) 81 (3) 3448-3111; Mexico, Central America, & Caribbean 52 (5) 666-6333;
The Netherlands +31 23 56 95555; Norway +47 22 07 07 00; People's Republic of China 86 (10) 6235 1230; Republic of Korea 82 (2) 528-5299; South Africa (27 11) 651-5222; Spain & Portugal +34 91 372 6000;
Sweden +46 8 477 65 00; Switzerland +41 (41) 729 36 40; Taiwan 886 (2) 2722-9622; United Kingdom & Eire +44 (0) 1628 403300; USA 1 (800) 426-2200.

From other areas, contact: Tektronix, Inc. Export Sales, P.O. Box 500, M/S 50-255, Beaverton, Oregon 97077-0001, USA 1 (503) 627-6877.



Copyright © 1999, Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

